






TONDA

GELATO "4 stagioni" "4 seasons" GELATO DISPLAY CASE



CARATTERISTICHE TECNICHE	OPTIONAL	TECHNICAL SPECIFICATIONS	OPTIONALS
<ul style="list-style-type: none"> - vasca monoblocco schiumata in poliuretano iniettato a 40 kg/m³ - chiusura ermetica tramite vetro camera temperato, pirolitico e riscaldato - illuminazione LED perimetrale - termostato elettronico con visualizzatore temperatura e ripetitore lato cliente - sistema di rotazione nei due sensi con comandi a pedale o manuale - refrigerazione ventilata con evaporatore semicircolare - sbrinamento a gas caldo - gestione degli sbrinamenti tramite sistema RDF (Reduced Defrosting Frequency) 	<ul style="list-style-type: none"> - versione 4 stagioni: grazie al pulsante di commutazione è possibile con un semplice "click" passare dalla funzione gelateria BT (= temperatura negativa -12°C/-18°C) alla funzione pasticceria o snack TN (= temperatura positiva +4°C/+8°C) - vassoi inox porta torte - lavaporizzatore - unità condensatrice remota - sbrinamento a inversione di ciclo - tropicalizzazione: unità condensatrice remota testata a +43°C ambiente 	<ul style="list-style-type: none"> - monobloc foam tank insulated with injected polyurethane (40 kg/m³) - airtight closure with heated, tempered, pyrolytic, double glass - LED lighting - electronic thermostat with temperature display and relative repeater on customer's side - 2-way rotation, with pedal or manual controls - ventilated refrigeration system with semicircular evaporator - hot gas defrosting system - defrosting controlled by RDF system (Reduced Defrosting Frequency) 	<ul style="list-style-type: none"> - "4 Seasons" version: by just clicking the change button the case can be turned from gelato (BT = low temperature -12°C/-18°C) to pastry (TN = positive temperature +4°C/+8°C) - stainless steel cakes tray - scoop washer - remote condensing unit - reverse cycle defrosting system - tropicalization: remote condensing unit tested at +43°C / 109.4°F ambient temperature

SEZIONI SECTION VIEWS




BASE TONDA / ROUND BASE

L 1350 / 53.14"


L 1500 / 59.05"

TONDA UC


con unità condensatrice a bordo with built-in air-cooled condensing unit



BASE TONDA / ROUND BASE



L 1350 / 53.14"




L 1500 / 59.05"

TONDA NUC


senza unità condensatrice without condensing unit








BASE TONDA / ROUND BASE



L 1350 / 53.14"



L 1500 / 59.05"

A1	A2	A1+B+C	A2+B+C	B+C
				
12	12	15	15	18
Capienza vaschetta A1 A1 pan capacity	Capienza vaschetta A2 A2 pan capacity	Capienza vaschetta A1+B+C A1+B+C pan capacity	Capienza vaschetta A2+B+C A2+B+C pan capacity	Capienza vaschetta B+C B+C pan capacity
A1 - H 120 mm / 4.72" 5 L	A2 - H 165 mm / 6.5" 7 L	A1 - H 120 mm / 4.72" 5 L B - H 160 mm / 6.3" 4 L C - H 165 mm / 6.5" 5 L	A2 - H 165 mm / 6.5" 7 L B - H 160 mm / 6.3" 4 L C - H 165 mm / 6.5" 5 L	B - H 160 mm / 6.3" 4 L C - H 165 mm / 6.5" 5 L

DIMENSIONI, PESO E IMBALLO DIMENSIONS, WEIGHT AND PACKAGING

MODELLO MODEL	LUNGHEZZA LENGTH		PROFONDITÀ DEPTH		PESO WEIGHT		DIMENSIONE IMBALLO PACKAGING DIMENSIONS		PESO con imballo CRATED WEIGHT	
	mm	in	mm	in	kg	lb	mm	in	kg	lb
BASE TONDA	1356	53.39"	1405	55.31"	300	661	1664x1664xH1309	65.5"x65.5"xH51.5"	389	858
L 1350	1362	53.62"	1405	55.31"	300	661	1664x1664xH1309	65.5"x65.5"xH51.5"	389	858
L 1500	1512	59.53"	1405	55.31"	300	661	1664x1664xH1309	65.5"x65.5"xH51.5"	389	858

DATI TECNICI TECHNICAL SPECIFICATIONS

MODELLO MODEL		POTENZA COMP. HP	BREAKER SIZE	MCA	MOP	RESA CAPACITY	CLASSE CLIMATICA CLIMATE CLASS			TEMPERATURA DI ESERCIZIO OPERATING TEMPERATURE		
		HP	A	A	A	W/h -30°C	BTU/h -22°F	°C	°F	U.R. R.H.	°C	°F
BASE TONDA		2	15	12	17	1500	5.115	35°C	95°F	60%	-2°C; -18°C	+28.4°F; -0.4°F
L 1350		2	15	12	17	1500	5.115	35°C	95°F	60%	-2°C; -18°C	+28.4°F; -0.4°F
L 1500		2	15	12	17	1500	5.115	35°C	95°F	60%	-2°C; -18°C	+28.4°F; -0.4°F

MODELLO MODEL		POTENZA ASSORBITA CURRENT CONSUMPTION	RESA COOLING CAPACITY	CLASSE CLIMATICA CLIMATE CLASS			TEMPERATURA DI ESERCIZIO OPERATING TEMPERATURE	
		trifase 400/3/50	monofase 230/1/50	trifase 400/3/50	monofase 230/1/50	°C	°F	U.R. R.H.
BASE TONDA		1625 4.48	1910 10.03	1200 4.092	1750 5.968	35°C	95°F	60%
L 1350		1625 4.48	1910 10.03	1200 4.092	1750 5.968	35°C	95°F	60%
L 1500		1625 4.48	1910 10.03	1200 4.092	1750 5.968	35°C	95°F	60%

MODELLO MODEL		POTENZA ASSORBITA CURRENT CONSUMPTION	RESA COOLING CAPACITY	CLASSE CLIMATICA CLIMATE CLASS			TEMPERATURA DI ESERCIZIO OPERATING TEMPERATURE	
		trifase 400/3/50	monofase 230/1/50	trifase 400/3/50	monofase 230/1/50	°C	°F	U.R. R.H.
BASE TONDA		1910 5.98	1580 5.387	1580 5.387	1580 5.387	35°C	95°F	60%
L 1350		1910 5.98	1580 5.387	1580 5.387	1580 5.387	35°C	95°F	60%
L 1500		1910 5.98	1580 5.387	1580 5.387	1580 5.387	35°C	95°F	60%

MODELLO MODEL		POTENZA ASSORBITA CURRENT CONSUMPTION	RESA COOLING CAPACITY	CLASSE CLIMATICA CLIMATE CLASS			TEMPERATURA DI ESERCIZIO OPERATING TEMPERATURE	
		trifase 400/3/50	monofase 230/1/50	trifase 400/3/50	monofase 230/1/50	°C	°F	U.R. R.H.
BASE TONDA		1910 5.98	1580 5.387	1580 5.387	1580 5.387	35°C	95°F	60%
L 1350		1910 5.98	1580 5.387	1580 5.387	1580 5.387	35°C	95°F	60%
L 1500		1910 5.98	1580 5.387	1580 5.387	1580 5.387	35°C	95°F	60%

MODELLO MODEL		POTENZA ASSORBITA CURRENT CONSUMPTION	RESA COOLING CAPACITY	CLASSE CLIMATICA CLIMATE CLASS			TEMPERATURA DI ESERCIZIO OPERATING TEMPERATURE	
		trifase 400/3/50	monofase 230/1/50	trifase 400/3/50	monofase 230/1/50	°C	°F	U.R. R.H.
BASE TONDA		1910 5.98	1580 5.387	1580 5.387	1580 5.387	35°C	95°F	60%
L 1350		1910 5.98	1580 5.387	1580 5.387	1580 5.387	35°C	95°F	60%
L 1500		1910 5.98	1580 5.387	1580 5.387	1580 5.387	35°C	95°F	60%